

6311E



MATERIAL SAFETY DATA SHEET

EQUILON MSDS: 6311E-06 01/04/99

SHELL MVI 200 NEUTRAL

TELEPHONE NUMBER:

24 HOUR EMERGENCY ASSISTANCE

EQUIVA SERVICES: 877-276-7283

CHEMTREC: 800-424-9300

GENERAL MSDS ASSISTANCE

877-276-7285

NAME AND ADDRESS

EQUILON ENTERPRISES LLC

PRODUCT STEWARDSHIP

P.O. BOX 674414

HOUSTON, TX 77267-4414

SECTION I NAME

PRODUCT: SHELL MVI 200 NEUTRAL

CHEM NAME: HYDROTREATED HEAVY NAPHTHENIC DISTILLATE

CHEM FAMILY: PETROLEUM HYDROCARBON; BASE STOCK

SHELL CODE: 68230

HEALTH HAZARD: 0 FIRE HAZARD: 1 REACTIVITY: 0

SECTION II-A INGREDIENTS

NO.	COMPOSITION	CAS NO.	PERCENT
P	SHELL MVI 200 NEUTRAL		
1	HIGHLY REFINED PETROLEUM OIL	64742-52-5	100

NFPA HAZARD RATING: HEALTH 0 FIRE 1 REACTIVITY 0

SECTION II-B ACUTE TOXICITY DATA

NO.	ACUTE ORAL LD50	ACUTE DERMAL LD50	ACUTE INHALATION LC50
P	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE
1.	>5.0 G/KG, RAT	>2.0 G/KG, RABBIT	NOT AVAILABLE

* BASED ON API TESTING

SECTION III HEALTH INFORMATION

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

EYE CONTACT: BASED ON PRODUCT TESTING PRODUCT IS NON-IRRITATING TO THE EYES.

SKIN CONTACT: BASED ON PRODUCT TESTING PRODUCT IS NON-IRRITATING TO THE SKIN. PROLONGED AND REPEATED CONTACT MAY LEAD TO VARIOUS SKIN DISORDERS SUCH AS DERMATITIS, OIL ACNE OR FOLLICULITIS.

INHALATION: INHALATION OF VAPORS (GENERATED AT HIGH TEMPERATURES ONLY) OR OIL MIST FROM THIS PRODUCT MAY CAUSE MILD IRRITATION OF THE UPPER RESPIRATORY TRACT.

INGESTION: BASED ON PRODUCT TESTING PRODUCT IS CONSIDERED NO MORE THAN SLIGHTLY TOXIC IF SWALLOWED.

SIGNS AND SYMPTOMS: IRRITATION AS NOTED ABOVE.

AGGRAVATED MEDICAL CONDITIONS:

PREEEXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS:

THIS PRODUCT AND ITS COMPONENTS ARE NOT CLASSIFIED AS CARCINOGENS BY INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC), NATIONAL TOXICOLOGY PROGRAM (NTP) OR OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA).

SECTION IV OCCUPATIONAL EXPOSURE LIMITS

COMP NO.	OSHA PEL/TWA	PEL/CEILING	ACGIH TLV/TWA	TLV/STEL	OTHER
P	5 MG/M3*	NONE	5 MG/M3*	10 MG/M3*	

*OIL MIST, MINERAL

SECTION V EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: FLUSH EYES WITH WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING AND WIPE EXCESS OFF. WASH WITH SOAP AND WATER OR A WATERLESS HAND CLEANER FOLLOWED BY SOAP AND WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION.

INHALATION: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING. IN GENERAL NO TREATMENT IS NECESSARY UNLESS LARGE QUANTITIES OF PRODUCT ARE INGESTED. HOWEVER, GET MEDICAL ADVICE.

NOTE TO PHYSICIAN: IN GENERAL, EMESIS INDUCTION IS UNNECESSARY IN HIGH VISCOSITY, LOW VOLATILITY PRODUCTS, I.E., MOST OILS AND GREASES.

SECTION VI **SUPPLEMENTAL HEALTH INFORMATION**

NONE IDENTIFIED.

SECTION VII **PHYSICAL DATA**

BOILING POINT (DEG F): >550 SPECIFIC GRAVITY (H2O = 1): 0.9071 VAPOR PRESSURE (MM HG): 12 <0.1

MELTING POINT (DEG F): +20 (POUR POINT) SOLUBILITY IN WATER: NEGLIGIBLE VAPOR DENSITY (AIR = 1) NOT AVAILABLE

VISCOSITY: 38-43
CS @ 104 DEG F)

EVAPORATION RATE (NORMAL BUTYL ACETATE = 1): NOT AVAILABLE

APPEARANCE AND ODOR: WHITE LIQUID. SLIGHT HYDROCARBON ODOR.
PHYS/CHEM PROPERTIES: SEE ABOVE FOR DETAILS

SECTION VIII **FIRE AND EXPLOSION HAZARDS**

FLASH POINT AND METHOD 310 DEG F (PMCC)
FLAMMABLE LIMITS/PERCENT VOLUME IN AIR: LOWER: N/AV HIGHER: N/AV

EXTINGUISHING MEDIA:

USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:

MATERIAL WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONFINED FIRE-SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE-PRESSURE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

NONE IDENTIFIED

SECTION IX **REACTIVITY**

STABILITY: HAZARDOUS POLYMERIZATION WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID:

AVOID HEAT, OPEN FLAMES AND OXIDIZING MATERIALS.

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT ON THE COMBUSTION CONDITIONS. A COMPLEX MIXTURE OF AIRBORNE SOLID, LIQUID, PARTICULATES AND GASES WILL EVOLVE WHEN THIS MATERIAL UNDERGOES PYROLYSIS OR COMBUSTION. CARBON MONOXIDE AND OTHER UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED UPON COMBUSTION.

SECTION X **EMPLOYEE PROTECTION**

RESPIRATORY PROTECTION:

IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SECTION IV) USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29 CFR 1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES.

PROTECTIVE CLOTHING:

WEAR CHEMICAL RESISTANT GLOVES AND OTHER PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE PROLONGED SKIN CONTACT. NO SPECIAL EYE PROTECTION IS ROUTINELY NECESSARY. TEST DATA FROM PUBLISHED LITERATURE AND/OR CLOTHING MANUFACTURERS INDICATE THE BEST PROTECTION IS PROVIDED BY NITRILE GLOVES.

ADDITIONAL PROTECTIVE MEASURES

NONE IDENTIFIED

SECTION XI **EMPLOYEE PROTECTION**

SPILL OR LEAK PROCEDURES:

MAY BURN ALTHOUGH NOT READILY IGNITABLE. USE CAUTIOUS JUDGMENT WHEN CLEANING UP LARGE SPILLS. *** LARGE SPILLS *** WEAR RESPIRATOR AND PROTECTIVE CLOTHING AS APPROPRIATE. SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ADSORBENT SUCH AS CLAY, SAND, OR OTHER SUITABLE MATERIALS; DISPOSE OF PROPERLY. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE. *** SMALL SPILLS *** TAKE UP WITH AN ABSORBENT MATERIAL AND DISPOSE OF PROPERLY.

SECTION XII **SPECIAL PRECAUTIONS**

MINIMIZE PROLONGED SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES, INCLUDING SHOES, THAT CANNOT BE DECONTAMINATED.

STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILLATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

SECTION XIII **TRANSPORTATION REQUIREMENTS**

DEPARTMENT OF TRANSPORTATION CLASSIFICATION:

NOT HAZARDOUS BY D.O.T. REGULATIONS

DOT PROPER SHIPPING NAME: NOT APPLICABLE

OTHER REQUIREMENTS: NOT APPLICABLE

SECTION XIV **OTHER REGULATORY CONTROLS**

THIS PRODUCT IS LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL SUBSTANCES.

PROTECTION OF STRATOSPHERIC OZONE (PURSUANT TO SECTION 611 OF THE CLEAN AIR ACT AMENDMENTS OF 1990): PER 40 CFR PART 82, THIS PRODUCT DOES NOT CONTAIN NOR WAS IT DIRECTLY MANUFACTURED WITH ANY CLASS I OR CLASS II OZONE DEPLETING SUBSTANCES.

IN ACCORDANCE WITH SARA TITLE III, SECTION 313, THE ATTACHED ENVIRONMENTAL DATA SHEET (EDS) SHOULD ALWAYS BE COPIED AND SENT WITH THE MSDS.

SECTION XV **STATE REGULATORY INFORMATION**

<u>STATE LISTED COMPONENT</u>	<u>CAS NO</u>	<u>PERCENT</u>	<u>STATE CODE</u>
-------------------------------	---------------	----------------	-------------------

BASED ON INFORMATION AVAILABLE, THIS PRODUCT DOES NOT CONTAIN ANY CHEMICAL SUBSTANCE LISTED ON A CHEMICAL SPECIFIC STATE LIST.

SECTION XVI **SPECIAL NOTES**

REVISIONS WERE MADE IN SECTION XV.

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE

6311E

TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT DATA. IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF EQUIVA SERVICES, LLC AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF EQUIVA SERVICES, LLC.



ENVIRONMENTAL DATA SHEET

EQUILON EDS: 6311E

SHELL MVI 200 NEUTRAL

TELEPHONE NUMBER:

24 HOUR EMERGENCY ASSISTANCE

EQUIVA SERVICES: 877-276-7283

CHEMTREC: 800-424-9300

GENERAL MSDS ASSISTANCE

877-276-7285

NAME AND ADDRESS

EQUILON ENTERPRISES

PRODUCT STEWARDSHIP

P.O. BOX 674414

HOUSTON, TX 77267-4414

PRODUCT CODE: 68230

SECTION I PRODUCT COMPOSITION

<u>NO.</u>	<u>COMPOSITION</u>	<u>CAS NO.</u>	<u>PERCENT</u>
P	SHELL MVI 200 NEUTRAL		
1	HIGHLY REFINED PETROLEUM OIL	64742-52-5	100

SECTION II SARA TITLE III INFORMATION

NO. EHS RQ EHS TPQ SEC-313 313 CATEGORY 311/312 CATEGORY

=====

BASED ON THE DATA AVAILABLE THIS PRODUCT IS NOT REGULATED BY SARA,
TITLE III

- *1 = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC 302
- *2 = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC 302
- *3 = TOXIC CHEMICAL, SEC 313
- *4 = CATEGORY AS REQUIRED BY SEC 313 (40 CFR 372.65 C), MUST BE USED ON TOXIC
RELEASE INVENTORY FORM
- *5 = CATEGORY (FOR AGGREGATE REPORTING REQUIREMENTS UNDER SARA 311, 312)
 - HEALTH: H-1 = IMMEDIATE (ACUTE) HEALTH HAZARD
 - H-2 = DELAYED (CHRONIC) HEALTH HAZARD
 - PHYSICAL: P-3 = FIRE HAZARD
 - P-4 = SUDDEN RELEASE OF PRESSURE HAZARD
 - P-5 = REACTIVE HAZARD

SECTION III ENVIRONMENTAL RELEASE INFORMATION

THIS PRODUCT IS COVERED BY EPA'S COMPREHENSIVE ENVIRONMENTAL RESPONSE,
COMPENSATION AND LIABILITY ACT (CERCLA) PETROLEUM EXCLUSION. THEREFORE
RELEASES TO AIR, LAND, OR WATER ARE NOT REPORTABLE UNDER CERCLA
("SUPERFUND"). HOWEVER UNDER SECTION 311 OF EPA'S CLEAN WATER ACT (CWA),
THIS PRODUCT IS CONSIDERED AN OIL. AS SUCH, SPILLS INTO OR LEADING TO
SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE
CENTER, 800-424-8802.

THIS PRODUCT IS AN OIL UNDER 49 CFR (DOT) PART 130. IF SHIPPED BY RAIL OR
HIGHWAY IN A TANK WITH A CAPACITY OF 3,500 GALLONS OR MORE, IT IS SUBJECT TO
THE REQUIREMENTS OF PART 130. MIXTURE SOLUTIONS IN WHICH THIS PRODUCT IS
PRESENT AT 10% OR MORE MAY ALSO BE SUBJECT TO THIS RULE.

SECTION IV RCRA INFORMATION

IF THIS PRODUCT BECOMES A WASTE, IT WOULD NOT BE A HAZARDOUS WASTE BY RCRA
CRITERIA (40 CFR 261). PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN
COMPLIANCE WITH LOCAL REGULATIONS.

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE
TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT DATA. IT IS
PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD
COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE
INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH
RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED
HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY,
PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY
COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH

6311E

RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF EQUIVA SERVICES, LLC AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF EQUIVA SERVICES, LLC.

KAREN G. HAYNES

EQUIVA SERVICES LLC

P.O. BOX 674414

HOUSTON, TX 77267-4414

FOR ADDITIONAL INFORMATION ON THIS ENVIRONMENTAL DATA PLEASE CALL
(877) 276-7285

FOR EMERGENCY ASSISTANCE PLEASE CALL
EQUIVA SERVICES LLC: (877) 276-7283
CHEMTREC: (800) 424-9300